


MIST M31

RTD Temperature Transmitter
w/Remote Probe & M12 Micro-Connector



USA Patent No.: 7,223,014
CDN Patent No.: 2,561,570

Custom Builder

MODEL 1 2 3 4 5 6 7 8 9 10 11

M31 - - - - - - - - - **0** - - -

BOX1 CODE	Calibrated Temperature Range
05	0°C to 50°C (32/122°F)
10	0°C to 100°C (32/212°F)
15	0°C to 150°C (32/302°F)
20	0°C to 200°C (32/392°F)
55	-50°C to 50°C (-58/122°F)
51	-50°C to 150°C (-58/302°F)
52	-50°C to 200°C (-58/392°F)
L*	-50°C to 200°C (-58/392°F)
H*	-200°C to 600°C (-328/1112°F)

* Code **L** & **H** are not factory calibrated. Requires customer calibration using the **MIST PKIT**.

Notes:

- MIST Temperature Sensors™ are factory calibrated at one point to an accuracy of ±0.12°@0°C or better. See MIST specs.
- For non-standard temperature ranges, indicate desired value in °C or °F in Box1 or see web site www.intempco.com.
- Order **MIST PKIT** for sensor customization.

BOX2 CODE	Output
LP	4-20 mA loop, upscale burnout (std.)
LD	4-20 mA loop, downscale burnout
VA	0-5 Vdc, 3-wire
VB	1-5 Vdc, 3-wire
VD	0-10 Vdc, 3-wire

Other outputs available. Consult factory.

BOX3 CODE	Probe Diameter "D"
B	1/8"
C	3/16"
D	1/4"
F	3/8"
H	1/2"

Other diameters available. Consult factory.

BOX4 CODE	Probe Material
S	Stainless steel 316/316L

Other materials available. Consult factory.

BOX5 CODE	Probe Length "L"
---	In 0.1" increments Ex.: 065 = 6.5" long

BOX6 CODE	Extension Cable Type "E"
PV	PVC insulation, stranded cond. 90°C (195°F) max.
TF	Teflon® insulation, stranded cond. 200°C (392°F) max.
TA*	Teflon® with SS armor, 200°C (392°F) max.
TP	Teflon® with SS armor and polyolefin shrink, 90°C (195°F) max.
TT	Teflon® with SS armor and Teflon® shrink, 200°C (392°F) max.
TS*	Teflon® with SS overbraid, 200°C (392°F) max.

* Code **"TA"** & **"TS"** are preferred methods of construction due to strength factors.

BOX7 CODE	Extension Cable Length "E"
---	In feet Ex.: 060 = 60 feet long

BOX9 CODE	Fitting Type
0	None
A**S	Adjustable fitting*
Ferrule material : A = Stainless steel* B = Brass* T = Teflon® * Not readjustable with metal ferrule	
Fitting material : S = Stainless steel B = Brass Ex.: T14B = Teflon® ferrule, 1/4" NPT, Brass fitting	
Process NPT size : ** 18 = 1/8" NPT 14 = 1/4" NPT 38 = 3/8" NPT 12 = 1/2" NPT 34 = 3/4" NPT 44 = 1" NPT	

BOX10 CODE	Connector Type
MC	M12 Micro-Male Connector

Other types of connectors available. Consult factory.

BOX11 CODE	Extension Cable Length "H"
N	None
A2	Straight, 2 meters
A5	Straight, 5 meters
B2	Right angle, 2 meters
B5	Right angle, 5 meters